



# PALADIN®

BRADCO

[www.paladinattachments.com](http://www.paladinattachments.com)



## GROUND SHARK®

### HEAVY DUTY BRUSH CUTTERS FOR SKID STEERS

Designed to clear medium to heavy brush and hardwoods up to 7" in diameter. When the exclusive, patented retractable forward shield comes in contact with a tree, it moves up and back to expose the entire cutting edge of each blade while protecting the operator from flying debris.

# GROUND SHARK®

## HEAVY DUTY BRUSH CUTTERS FOR SKID STEER LOADERS

### FEATURES

- Deck steps on both sides to facilitate different carriers with entry on left or right side.
- The hydraulic hoses can be easily rerouted to allow hookup to multiple machine brands.
- Exclusive patented retractable cutting forward shield. When using the Ground Shark on brush/trees that are bigger than 4" in diameter, the shield will retract on its own to allow for maximum performance.
- Serrated Edges on Push Bar and Chassis front corners enable better control when moving material.
- The motor and valve assembly are fully shielded preventing contact with debris.
- Three 5/8" thick bevel edge blades on 66" model and four on 72" model. Forged from top grade steel for excellent cutting in most applications.
- Direct drive motor for efficient performance.
- The Ground Shark line of brush cutters include special hydraulic valving to shut the cutter head down quickly and safely. There is a distinct audible sound during the shutdown which will indicate to the operator that the blades are coming to a stop.
- Bi-directional operation allows operators to utilize both edges of each blade without having to rotate or change blades.
- Optional MulchPower™ gauge is visible to the operator and helps prevent excessive stalling and overheating.
- Blade retention bolt hex shank is design to prevent the bolt from rotating under extreme cutting conditions.
- Bolt on carbide stump grinding teeth increases mulching performance and take the stump down to ground level.
- .25" thick steel deck design.
- Bolt-on replaceable skid shoes.

### SPECIFICATIONS

	GS66HD			GS72HD		
ORDER CODE	31766-0022	31766-9903	31766-9925	31772-0022	31772-9903	31772-9925
COUPLER SIZE	1/2 IN.	5/8 IN.	3/4 IN.	1/2 IN.	5/8 IN.	3/4 IN.
OVERALL HEIGHT	28.13 IN.	28.13 IN.	28.13 IN.	28.13 IN.	28.13 IN.	28.13 IN.
OVERALL WIDTH	71.13 IN.	71.13 IN.	71.13 IN.	77.13 IN.	77.13 IN.	77.13 IN.
OVERALL LENGTH	81.75 IN.	81.75 IN.	81.75 IN.	85.59 IN.	85.59 IN.	85.59 IN.
CUTTING WIDTH	66 IN.	66 IN.	66 IN.	72 IN.	72 IN.	72 IN.
MINIMUM CUTTING HEIGHT	2.5* IN.	2.5* IN.	2.5* IN.	2.5* IN.	2.5* IN.	2.5* IN.
MINIMUM STUMP GRINDING HEIGHT	.75 IN.	.75 IN.	.75 IN.	.5 IN.	.5 IN.	.5 IN.
CUTTING CAPACITY	7 IN.	7 IN.	7 IN.	7 IN.	7 IN.	7 IN.
DECK THICKNESS	.25 IN.	.25 IN.	.25 IN.	.25 IN.	.25 IN.	.25 IN.
RECOMMENDED FLOW	20-34 GPM	20-34 GPM	20-34 GPM	20-34 GPM	20-34 GPM	20-34 GPM
REQUIRED LIFT CAPACITY	2200 LBS	2200 LBS	2200 LBS	2200 LBS	2200 LBS	2200 LBS
WEIGHT	1605 LBS	1605 LBS	1605 LBS	1800 LBS	1800 LBS	1800 LBS

\*Angled Front Allows Cut to Ground Level

