



PALADIN®

BRADCO

www.paladinattachments.com



GROUND SHARK®

STANDARD DUTY BRUSH CUTTERS FOR SKID STEERS

The Ground Shark® Standard Duty Brush Cutter is designed to clear light to medium density brush and hardwoods up to 4" diameter. The Ground Shark direct drive system runs efficiently, smooth and quiet while cutting the toughest material. Low-profile design slips easily under fences. The perfect general purpose brush cutter for routine land maintenance.

GROUND SHARK[®]

STANDARD DUTY BRUSH CUTTERS FOR SKID STEER LOADERS

FEATURES

- Dual pressure reliefs on the hydraulic motor allow for bi-directional operation protect against pressure spikes that could damage the drive system.
- Bi-directional forged steel blades (3) allow operator to cut in both directions extending operational life and reducing maintenance cost by cutting heavier brush in one-direction and grass or smaller vegetation in the other.
- The Ground Shark line of brush cutters include special hydraulic valving to shut the cutter head down quickly and safely. There is a distinct audible sound during the shutdown which will indicate to the operator that the blades are coming to a stop.
- Direct drive motor for efficient performance.
- Deck steps on both sides to facilitate different carriers with entry on left or right side. Hose routing can also be configured on either side.
- Deck Leading Edge Radius Guide enables smoother material glide path.
- .25 thick steel deck design.
- Bolt-on replaceable skid shoes.
- An optional MulchPower™ gauge is visible to the operator and helps prevent excessive stalling and overheating.
- Optional dual wheel kits are available that mount to the underside of the front deck to keep the blades off the ground and prevent scalping.

SPECIFICATIONS

| | GS60SD | GS72SD (A) | GS72SD (B) | GS72SD (C) | GS78SD (A) | GS78SD (B) | GS78SD (C) |
|------------------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| ORDER CODE | 30360A-0022 | 30372A-0022* | 30372B-0022* | 30372C-0022* | 30378A-0022* | 30378B-0022* | 30378C-0022* |
| COUPLER SIZE | 1/2 IN. | 1/2 IN. | 1/2 IN. | 1/2 IN. | 1/2 IN. | 1/2 IN. | 1/2 IN. |
| OVERALL HEIGHT | 24 IN. | 24 IN. | 24 IN. | 27 IN. | 24 IN. | 24 IN. | 27 IN. |
| OVERALL WIDTH | 64 IN. | 76 IN. | 76 IN. | 76 IN. | 82 IN. | 82 IN. | 82 IN. |
| OVERALL LENGTH | 76 IN. | 88 IN. | 88 IN. | 88 IN. | 9 IN. | 94 IN. | 94 IN. |
| CUTTING WIDTH | 60 IN. | 72 IN. | 72 IN. | 72 IN. | 78 IN. | 78 IN. | 78 IN. |
| MINIMUM CUTTING HEIGHT | 2 IN. | 2 IN. | 2 IN. | 2 IN. | 2 IN. | 2 IN. | 2 IN. |
| CUTTING CAPACITY | 4 IN. | 4 IN. | 4 IN. | 4 IN. | 4 IN. | 4 IN. | 4 IN. |
| DECK THICKNESS | .25 IN. | .25 IN. | .25 IN. | .25 IN. | .25 IN. | .25 IN. | .25 IN. |
| RECOMMENDED FLOW | 15-25 GPM | 15-25 GPM | 26-32 GPM | 33-40 GPM | 15-25 GPM | 26-32 GPM | 33-40 GPM |
| REQUIRED LIFT CAPACITY | 1200 LBS | 1400 LBS | 1400 LBS | 1500 LBS | 1500 LBS | 1500 LBS | 1600 LBS |
| WEIGHT | 1120 LBS | 1280 LBS | 1280 LBS | 1320 LBS | 1360 LBS | 1365 LBS | 1405 LBS |

* 5/8" And 3/4" Coupler Models Available, Please Contact Your Local Paladin Rep for More Information

